

The Impact 90 is a range of high-end professional downlights and is appreciated for its light comfort, performance and many customisation options. It takes a chrome cone. Also available with matt silver cone.



Artikelnummer: 3113250

SUMMARY SPECS

| | |
|----------------------|----------------|
| Mounting | : recessed |
| Adjustable | : no |
| Fixture light output | : 700lm |
| Driver | : non dimmable |
| System power | : 9W |
| Life | : 80000h |
| L./B. values | : L90/B10 |
| Color housing | : white |
| Color cone | : chrome |
| Cover | : no |
| Protection | : IP44 |

MATERIALS

| | |
|----------------|----------------------------|
| Material trim | : Aluminum |
| Cover material | : Aluminum & Polycarbonate |

SIZE AND WEIGHT

| | |
|-----------------|---------|
| Diameter | : 110mm |
| Ceiling cut out | : 93mm |
| Recess depth | : 85mm |

TECHNICAL LIGHTING DATA

| | |
|----------------------|-------------|
| Light distribution | : symmetric |
| Reflector type | : Reflector |
| Fixture light output | : 700lm |
| Color temperature | : 3000K |
| Color tolerance | : 3 SDCM |
| Color accuracy | : CRI>90 |
| Beamangle | : 40° |
| Glare ratio | : <8 |

ELECTRICAL DATA

| | |
|---------------------------------|----------------|
| Driver | : non dimmable |
| Driver (integrated or external) | : external |
| Connection | : europlug |
| Terminal | : europlug |
| Power factor | : >0,9 |
| System power | : 9W |
| No of fixtures in C13 fuse | : 37x/B16 |
| Emergency unit | : no |