

The Inplano DUAL UGR19 LED-panel has a connection for both 3000K AND 4000K. This offers the possibility to choose the color during installation. Especially in renovation were the 4000K may be more preferred against existing 3000K. Applicable in working areas with computer screens (like offices and class rooms).



Artikelnummer: 1015605

SUMMARY SPECS

| | |
|----------------------|-----------------|
| Mounting | : recessed |
| Adjustable | : no |
| Fixture light output | : 3600lm |
| Driver | : DALI dimmable |
| System power | : 36W |
| Life | : 50000h |
| L./B. values | : L80/B20 |
| Color housing | : white |
| Protection | : IP20 |

MATERIALS

| | |
|----------------|------------|
| Cover material | : Alu/PMMA |
|----------------|------------|

SIZE AND WEIGHT

| | |
|--------|------|
| Height | : 10 |
|--------|------|

TECHNICAL LIGHTING DATA

| | |
|----------------------|-------------------|
| Light distribution | : symmetric |
| Reflector type | : micro prismatic |
| Fixture light output | : 3600lm |
| Color temperature | : 3000/4000K |
| Color tolerance | : 3 SDCM |
| Color accuracy | : CRI>80 |
| Beamangle | : 120° |
| Glare ratio | : <19 |

ELECTRICAL DATA

| | |
|---------------------------------|------------------------|
| Driver | : DALI dimmable |
| Driver (integrated or external) | : external |
| Connection | : on driver |
| Terminal | : 5x1,5mm ² |
| Looping | : yes |
| Power factor | : >0,9 |
| System power | : 36W |
| No of fixtures in C13 fuse | : 30/C13 |
| Emergency unit | : no |