

The Inplano DUAL UGR19 LED-panel has a connection for both 3000K AND 4000K. This offers the possibility to choose the color during installation. Especially in renovation were the 4000K may be more preferred against existing 3000K. Applicable in working areas with computer screens (like offices and class rooms).



Artikelnummer: 1015505

#### SUMMARY SPECS

Mounting	: recessed
Adjustable	: no
Fixture light output	: 3600lm
Driver	: Zenlite bluetooth DIM
System power	: 36W
Life	: 50000h
L./B. values	: L80/B20
Color housing	: white
Protection	: IP20

#### MATERIALS

Cover material	: Alu/PMMA
----------------	------------

#### SIZE AND WEIGHT

Height	: 10
--------	------

#### TECHNICAL LIGHTING DATA

Light distribution	: symmetric
Reflector type	: micro prismatic
Fixture light output	: 3600lm
Color temperature	: 3000/4000K
Color tolerance	: 3 SDCM
Color accuracy	: CRI>80
Beamangle	: 120°
Glare ratio	: <19

#### ELECTRICAL DATA

Driver	: Zenlite bluetooth DIM
Driver (integrated or external)	: external
Connection	: on driver
Terminal	: 2x1,5mm <sup>2</sup>
Looping	: yes
Power factor	: >0,9
System power	: 36W
Emergency unit	: no