


The Inplano Pixel appeals with its louvre design the appearance of existing linear T5/T8 fluorescent solutions. This makes the Inplano Pixel the solution for replacement of traditional fluorescence fixtures. Very low glare (UGR<19), so suitable for application in e.g. offices.



Artikelnummer: 1000031

SUMMARY SPECS

Mounting	: recessed
Adjustable	: no
Fixture light output	: 3600lm
Driver	: non dimmable
System power	: 36W
Life	: 50000h
L./B. values	: L80/B20
Color housing	: white
Protection	: IP20

MATERIALS

Cover material	: ABS
----------------	-------

SIZE AND WEIGHT

Height	: 28
--------	------

TECHNICAL LIGHTING DATA

Light distribution	: symmetric
Reflector type	: louvre optics
Fixture light output	: 3600lm
Color temperature	: 3000K
Color tolerance	: 3 SDCM
Color accuracy	: CRI>80
Beamangle	: 90°
Glare ratio	: <19

ELECTRICAL DATA

Driver	: non dimmable
Driver (integrated or external)	: external
Connection	: on driver
Terminal	: 2x1,5mm ²
Looping	: no
Power factor	: >0,9
System power	: 36W
No of fixtures in C13 fuse	: 55/C13
Emergency unit	: no